技术资料

Fluke 714 热电偶校准器

主要特性

主要特点：
Fluke 714 热电偶校准器

产品概述: Fluke 714 热电偶校准器

The Fluke 714 Thermocouple Calibrator delivers outstanding performance, durability and reliability. The calibrator is compact, lightweight, and easy to carry. With a push button interface similar to the multifunction Fluke 750 Series documenting process calibrators, the 714 is easy to use. It is EMI tolerant, dust and splash resistant, and features a removable battery door for quick battery changes.

产品规格: Fluke 714 热电偶校准器

型号

Fluke 714

Fluke 714 Thermocouple Calibrator

热电偶温度校准器包括:

- C81Y 黄色防护套，有Flex-Stand™
- 操作说明卡 (14 种语言)
- 单节 9V 碱性电池

Optional accessories	Description
80PK-9 通用探头	80PK-9通用探头采用K型热电偶，适用于表面、空气和非腐蚀性气体测量，测量范围：-40 °C 至 260 °C。
Fluke TLK-220 US SureGrip 工业测试线	超值的SureGrip套件，适用于工业应用领域。包括两种大小的鳄鱼夹和尖锐的测试探头，连接可靠；还包括测试线以及一个可容纳并保护仪表和所有附件的大容量便携包
80PK-24 SureGrip 气体温度探头	80PK-24 SureGrip 气体温度探头采用K型热电偶，适用于空气和非腐蚀性气体测量，测量范围：-40至816°C。
80PK-27 SureGrip 工业表面温度探头	80PK-27 SureGrip™工业表面温度探头，兼容所有支持K型热电偶的测温仪，具有微型热电偶连接器，并具有参考冷结补偿，测量范围：-127 至 600 °C。

https://test.yed.njzhouji.com/product/过程校准及检测工具/温度校验仪/fluke-714

Fluke. *让您的工作畅通无阻。*

福禄克测试仪器（上海）有限公司 电话：400-810-3435
北京福禄克世禄仪器维修和服务有限公司 电话：400-615-1563
福禄克测试仪器（上海）有限公司上海维修中心 电话：021-54402301, 021-54401908分机269
福禄克测试仪器（上海）有限公司深圳第一特约维修点 电话：0755-86337229

©2025 福禄克公司
08/2025

未经许可，本文档禁止修改

https://test.yed.njzhouji.com/product/过程校准及检测工具/温度校验仪/fluke-714